RHLED LED Indoor Thermoplastic Remote Head



Project:	
Type:	
Catalog #:	



STANDARD



ILLUMINATION

- · Long lasting, efficient, ultra bright white LED lamp heads.
- 1.0 watt (8 LEDs x 0.125 watt) per head.
- High performance chrome-plated metalized reflector and plastic lens for optimal light distribution.
- Adjustable LED lamp heads provide optimal center-tocenter spacing.
- Optional high lumen heads are 1.5 watts (12 LEDs x 0.125 watt per head) and provide increased center-to-center spacing.

ELECTRICAL

 Powered from low voltage power source with low voltage wiring (not provided).

MOUNTING

- Universal mounting adapter plate included. Mounts to single-gang switch box.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.
- · Suitable for wall or ceiling mount.


HOUSING

 Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

WARRANTY / LISTING

- Five year warranty.
- UL Listed or damp locations (0°C − 50°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

DIMENSIONS



FIXTURE COMPATIBILITY CHART

Reference individual unit equipment specification sheets for remote load capacity availability.

BEST LIGHTING MODEL TYPE								
CADXR	CALEDCXTE-RC	CAR						
CEM-RC	CEU-RC	CKXTEU-RC						
CLPU	CWLEZXTE-RC	DXR						
E-1-RC	EM-RC	LEDSDXR627						
LEDTFX-2	NYDXR	RMCLPU-RC						
RMLEDCXTE-RC	RMR-16-65/125	CEMXTE						
CEXTEU	INDEMR	HLEMR						
INDCWLEZ	HLCWLEZ	CAEM						

ORDERING INFORMATION

Sample Part Number: RHLED1-MV

	MODEL	No. of HEADS		OPTIONS		VOLTAGE		COLOR		LAMP TYPE ¹	
¹ Wattage rating stated per head.	RHLED	1 2	Single Head Double Head	(blank) SDT	For Standard Non- Self-Diagnostic Fixtures For Use With Fixtures With A Self-Diagnostic Option	MV	For Use With 3.6V, 6V, 9.6V & 12V DC Power Source	(blank) B	White Black	(blank) HL	8 LEDs 1W 12 LEDs 1.5W